

METHOD AND APPARATUS FOR DOUBLE DATA RATE SERIAL ATA PHY INTERFACE

by Inventors

5 Ook Kim, Sungjoon Kim, Robert Norman, Chi Wai Ho, Frank Lee,
 Dongyun Lee, Gijung Ahn and Seung Ho Hwang

CROSS REFERENCE TO RELATED APPLICATIONS

10 [0001] This application claims the benefits of co-pending U.S. Provisional Patent
Application number 60/409,367 filed on September 6, 2002, and is incorporated
herein by reference.

FIELD OF THE INVENTION

15 [0002] The present invention relates to PC motherboard chipsets and more
particularly to connection schemes between PC motherboard chipsets and hard
disk drives.

BACKGROUND OF THE INVENTION

20 [0003] ATA (advanced technology attachment or AT attachment – a reference to
AT/286 computers) has been the standard internal storage interconnect for desktop
and mobile computers since the 1980's. ATA's relative simplicity, low cost and
high performance has enabled it to remain in use for an extended period of time.

[0004] Despite these advantages, a number of limitations exist. ATA uses a 5-volt
signal requirement. Use of this standard is becoming incompatible with cutting
edge integrated circuits that are designed to operate at a lower voltage. Also, ATA

requires a high pin count which necessitates a bulky ribbon cable. The high pin count is problematic for chip design and the ribbon cable impedes airflow which makes thermal design difficult. Finally, ATA data transfer rate is limited to about 100 megabytes/second maximum.

5 [0005] Due to those limitations, a new standard has been defined for the next generation ATA. This standard is called serial ATA or SATA for short. This new standard allows for data transfer speeds starting at 150 megabytes/second and ultimately up to 600 megabytes per second. Advantageously, it also employs a much thinner cable with a smaller pin count.

10 [0006] As the new SATA standard gains widespread use, undoubtedly there will be computer users who may wish to use both older style ATA Hard Disk Drives (HDDs) and SATA HDDs in one system. Figure 1 illustrates a prior art computer system **10** that employs ATA style HDDs. Included in the system is a CPU **20**, a motherboard chipset or South Bridge **30**, an ATA bus **40**, a first ATA HDD **50** and
15 a second ATA HDD **60**. In the ATA configuration, only one ATA bus is used and only 1 HDD can communicate to the CPU at a time.

[0007] Figure 2 shows a computer system **70** that uses the newer SATA configuration. Similar to the ATA setup, there is a CPU **20** and a South Bridge interface **30**. Also included is a first SATA HDD **80** and a second HDD SATA **90**.
20 Unlike the ATA configuration, each SATA HDD **80** and **90** are connected directly to the South Bridge via separate SATA links **90** and **100**.

[0008] It is readily recognized that, in the prior art, in order to use both style connectors in one system, more cables would need to be added or the SATA and ATA type connectors would need to be combined into one larger, more complex,
25 more expensive and unwieldy cable.

[0009] Accordingly, what is needed is a way easily connect an SATA HDD into an existing system containing ATA HDD's without having to add more cables or add to the pin count of the existing ATA connector.

SUMMARY OF THE INVENTION

[0010] The present invention provides a method and apparatus for adding a SATA HDD into an existing system containing ATA HDDs without having to add more cables or add to the pin count of the existing ATA connector.

5 [0011] A method for multiplexing control signals for disk drives, in accordance with an embodiment of the present invention, includes developing parallel control signals and developing serial control signals. At least one of the parallel control signals and the serial control signals are coupled to at least one of a parallel hard disk drive and a serial hard disk drive by a common control bus.

10 [0012] A disk drive controller, in accordance with another embodiment of the present invention, includes parallel logic developing parallel control signals and serial logic developing serial control signals. Also included is a multiplexer that couples at least one of the parallel control signals and the serial control signals to a common bus.

15 [0013] A method for doubling a data rate on a disk drive serial bus, in accordance with yet another embodiment of the present invention, includes developing a sampling data clock, developing a first data stream at a base data rate and developing a second data stream at the base data rate. The first data stream is multiplexed to a disk drive serial bus on a rising edge of the base data clock and
20 the second data stream is multiplexed to the disk drive serial bus on a falling edge of the base data clock, whereby the disk drive serial bus carries both the first data stream and the second data stream at effectively double the base data rate.

[0014] A method for encoding additional commands in a coding standard, in accordance with a final embodiment of the present invention, includes determining

at least one invalid command in used coding space of a coding standard; and determining unused coding space. The at least one invalid command is encoded in the used coding space and at least one command is encoded in the unused coding space.

- 5 [0015] An advantage of the present invention is that serial ATA hard disk drives can be added to an existing system utilizing ATA hard disk drives without adding to the pin count of a chipset. Additionally, the present invention provides for double data rate communication to serial ATA hard disk drives and for encoding additional commands in an unused space of a coding standard.
- 10 [0016] These and other advantages of the present invention will become apparent to those skilled in the art after reading the following descriptions and studying the various figures of the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] Figure 1 is a partial block diagram of a prior art computer system that employs ATA style HDD's.

5 [0018] Figure 2 is a partial block diagram of a computer system that employs SATA style HDDs.

[0019] Figure 3 is a partial block diagram of a computer system that utilizes both ATA and SATA style HDDs, in accordance with an embodiment of the present invention.

10 [0020] Figure 4 is a partial block diagram of a computer system that utilizes both ATA and SATA style HDDs, in accordance with another embodiment of the present invention.

[0021] Figure 5A is a circuit diagram for generating TxD and TBC signals, in accordance with the present invention.

15 [0022] Figure 5B is an alternate circuit diagram for generating TxD and TBC signals, in accordance with the present invention.

[0023] Figure 5C is a timing diagram for TxD and TBC, in accordance with the present invention.

[0024] Figure 6 is a circuit diagram which generates TxD and TBC for a
20 multiplexer, in accordance with the present invention.

[0025] Figure 7 is a block diagram of the PHY portion of the TBC and the TxD block, in accordance with the present invention.

[0026] Figure 8 is a timing diagram of RBC0, RBC1 and RxD, in accordance with the present invention.

[0027] Figure 9A is a block diagram illustrating a flow of data between a link and a PHY, in accordance with the present invention.

5 [0028] Figure 9B is a block diagram illustrating an implementation for generating an RBC signal, in accordance with the present invention.

[0029] Figure 9C is a timing diagram of RBC0 and RBC1 timing relationships in RXD and RBC calibration phases, in accordance with the present invention.

[0030] Figure 10 is a flowchart illustrating a method of calibrating differing clocks,
10 in accordance with the present invention.

[0031] Figure 11 is a timing diagram illustrating a DATA_READY signal generation, in accordance with the present invention.

[0032] Figure 12 is a flowchart illustrating a method encoding additional information in an unused coding space of a coding standard, in accordance with the
15 present invention.

[0033] Figure 13A is a flowchart illustrating a method for encoding additional information in an unused coding space of an 8B10B encoding scheme, in accordance with the present invention.

[0034] Figure 13B is an illustration of encoding additional information in an unused
20 coding space of an 8B10B encoding scheme, in accordance with the present invention.

[0035] Figure 14 is a block diagram illustrating pin encoding, in accordance with an embodiment of the present invention.

[0036] Figure 15 is a timing diagram illustrating a method of transmitting a double data rate, in accordance with an embodiment of the present invention.

5 [0037] Figure 16 is a timing diagram illustrating an SDR case when channel 0 is active for a power saving mode, in accordance with the present invention.

[0038] Figure 17 is a timing diagram illustrating an SDR case when channel 1 is active for a power saving mode, in accordance with the present invention.

[0039] Figure 18 is a timing diagram illustrating RBC0 and RBC1 when channel 0
10 is active for a power saving mode, in accordance with the present invention.

[0040] Figure 19 is a timing diagram illustrating RBC0 and RBC1 when channel 1 is active for a power saving mode, in accordance with the present invention.

[0041] Figure 20 illustrates a state diagram for channel 0 and channel 1 active/inactive modes, in accordance with the present invention.

15 [0042] Figure 21 is a block diagram of an SATA PHY chip, in accordance with the present invention.

[0043] Figure 22 is a detailed block diagram illustrating the hookup of the Rx encoders with a two-channel interface, in accordance with the present invention.

[0044] Figure 23A is a detailed block diagram illustrating the hookup of the Tx
20 encoders with a two-channel interface, in accordance with the present invention.

[0045] Figure 23B is a more detailed block diagram illustrating the hookup of the Tx encoders, in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0046] Figs. 1-2 were previously described with reference to the prior art.

[0047] Fig. 3 is a partial block diagram **110** of a computer system that utilizes both ATA and SATA style HDDs, in accordance with an embodiment of the present invention. Included is a PC motherboard chipset **120** that contains a multiplexer **130** that multiplexes signals from parallel ATA logic **140** and serial ATA logic **150**. Also included is an ATA connector **160** that connects to ATA HDD's **50** and **60** via an ATA cable **165**. Additionally, an SATA PHY **170** is coupled to the multiplexer **130** and SATA connectors **180**. Connectors **180** are coupled to SATA HDD's **80** and **90** via SATA cables **190**. Within the SATA PHY **170**, there is also a demultiplexer **200** and an SATA PHY sub-block **210**.

[0048] SATA PHY **200** can be configured as an interface between a chipset **120** and an SATA serial data HDD (**80** and **90**) as shown in Fig. 3. In this case, the chipset **120** has a built-in MUX **130** to control the data stream, which is used either for the ATA logic **140** or for the SATA logic **150**. For the ATA logic **140**, the internal MUX **130** operates at a very high speed and there is very little effect on the ATA operation. In the SATA logic **150**, it uses the same ports to communicate with SATA PHY **170**. However, in this case, the interface is no longer employing the ATA interface signaling scheme.

[0049] Fig. 4 is a partial block diagram **220** of a computer system **220** that utilizes both ATA and SATA style HDDs, in accordance with another embodiment of the present invention. In this embodiment, the ATA signals are routed through the SATA PHY **230** via the buffer **240**.

[0050] Fig. 5A is a circuit diagram **250** for generating TxD (Tx data) and TBC (Transmi Byte Clock) signals, in accordance with the present invention.

Flipflops(namely FF) **260** and **270** are coupled to channels A and channel B, respectively, as well as a 150 MHz clock. Channels A and B refer to two separate
 5 SATA HDD's. FFs **260** and **270** produce signals A' and B' that are subsequently coupled to Multiplexer(namely Mux) **280**. The output of mux **280** is coupled to FF **290** that is also coupled to a 300 MHz clock and produces the TxD output. Also included is a FF **300** that is coupled to a TBC' input and the 300 MHz clock and FF **300** produces a TBC output.

10 [0051] Figure 5B is an alternate circuit diagram for determining when to use a double data rate, in accordance with the present invention. Mux **320** is coupled to channel A, an output of FF **321** and ACT0. FF **330** is coupled to the output (A') of flipflop **320** and a 150 MHz clock. Similarly, FF **321** is coupled to channel B and the 150 MHz clock. Additionally, mux **340** is coupled to the outputs of FFs **321**
 15 and **330**. Finally, FF **350** is coupled to an output of mux **340** and mux **360** is coupled to the outputs of FFs **350** and **330**. In operation, when both ACT0 and ACT1 delivers a high signal (1), double data operation is employed.

[0052] Referring to Figs. 5C and 6, Fig. 5C is a timing diagram for TxD and TBC, in accordance with the present invention and Fig. 6 is a circuit diagram which
 20 generates TxD and TBC for multiplexer **130** (not shown), in accordance with the present invention. The Tx block in the PC motherboard chipset (LINK) **120** is generated by mux **370**. As long as the TBC clock **380** is generated by the same FFs **410** and **420**, the data(TxD) and clock (TBC) **390** will be aligned with each other. TxD **390** is sent to PHY (**170**/not shown). PHY **170** has a built-in PLL which is
 25 used for transmitting low jitter, high speed serial data. The PHY extracts TBC edge and extracts an optimum clock TXCLK' **400**. With this scheme, two channel data

can be also sent in a single ATA bus as well. With the high duration of the clock, data 'A' is sent and with the low duration of the clock, data 'B' is sent. The PLL can also be used for extracting the optimum clock phases for TXD 390 data latching point.

- 5 [0053] With further reference to Fig. 6, channels A and B are coupled to mux 370. FFs 410 and 420 are both coupled to a 300 MHz clock CLK. FF 410 is also coupled to an output of mux 370. In addition, buffers 430 and 440 are coupled to outputs of FFs 410 and 420, respectively.

10 [0054] Referring to Figs. 7 and 8, Fig. 7 is a block diagram of the PHY portion 170 of the TBC and the TxD block and Fig. 8 is a timing diagram of RBC0, RBC1 and RxD, both in accordance with the present invention. For the receiving portion of the data, two clock signals (RBC0 and RBC1) are generated to latch incoming data. RBC0 is used for extracting 'A' block data and RBC1 is used for extracting 'B' block data.

- 15 [0055] By using this scheme, two channels of SATA data can be sent on a single data line. For the generation 1 case defined in SATA specification, 150 Mbytes/sec data is transferred from LINK/chipset 120 to PHY 160, by using double data rate transmission, 300 Mbytes/sec total data speed is achieved. For the generation 2 case, total 600 Mbytes/sec total data speed is also achieved by having
20 two 300 Mbytes/sec data channels in the link. Even though the chipset 120 cannot deliver 600 Mbytes/sec for a general case, it can transmit data within such condition as short distance and minimum capacitance loading. Also, by having calibration phases during setup link time, test patterns can be transmitted and PHY detects channel skew between clocks and data, as will be discussed subsequently.
25 By having high-speed data input port for this link in the PHY block, reliable

transmission can be achieved by using moderate data and clock driver in the chipset.

[0056] In the RXD section, two clock signals such as RBC0 and RBC1 are generated from the PHY as shown in Fig. 8. These two clock lines signals are both channel A and channel B. As the link speed becomes higher, the optimum latching point for the RXD is very important to make a solid link between PHY 120 and LINK 170. To make it more robust over various operation conditions and PCB traces, a calibration scheme can be used.

[0057] In view of the foregoing, it will be appreciated that a method for multiplexing control signals for disk drives includes developing parallel control signals and developing serial control signals. At least one of the parallel control signals and the serial control signals are coupled to at least one of a parallel hard disk drive and a serial hard disk drive by a common control bus.

[0058] It will also be appreciated that a disk drive controller includes parallel logic developing parallel control signals and serial logic developing serial control signals. Also included is a multiplexer that couples at least one of the parallel control signals and the serial control signals to a common bus.

[0059] Fig. 9A is a block diagram illustrating a flow of data between a link 110 and a PHY 170, in accordance with the present invention. As can be seen, binary data flows between the link 110 and PHY 170. In order to keep the flow of data flowing correctly, calibration between the two blocks 110 and 170 needs to occur.

[0060] Fig. 9B is a block diagram 450 illustrating an implementation for generating an RBC signal, in accordance with the present invention. The RBC signal is used as part of the calibration technique that will be explained in more detail,

subsequently. Included in block diagram **450** is a PLL **460** coupled to a flipflop **470**. Flipflop **470** is also coupled to a logic **480**. Logic **480** responsive to a TxD signal and operative to develop an RxD signal.

[0061] Fig. 9C is a timing diagram of RBC0 and RBC1 timing relationships in RXD and RBC calibration phases, in accordance with the present invention. RBC0,1 is moved relative to the RXD in the calibration phase. In this mode, LINK **110** re-transmits received data through TX channel. By using adequate calibration test patterns, generated by the PHY, PHY can detect the optimum RBC0,1 and RXD data relationship. It can also detect channel skews between RBC0,1. The start and end of calibration can be timer operated such as shown in figure 10. However, some signals such as one bit of RXD or other signal bits can be used for this purpose as well.

[0062] Fig. 10 is a flowchart illustrating a method **485** of calibrating differing clocks, in accordance with the present invention. After a start operation **490**, a phase is chosen at operation **500**. A test is then sent for the chosen phase at operation **510** and the test is received at operation **520**. At a decision point **530**, it is checked to see if all phases have been tested. If not, the data rate is logged at operation **540** and the next phase is chosen at operation **500**. Operations **510**, **520** and **530** are then repeated. After all phases have been tested, the best edge for RBC has been calculated. One algorithm for this is to log those phases which has a specific bit errors, then the optimum phase is the mean value of phases, where bit error rate is zero, at operation **550**. This has been shown in figure 10B. The method then ends at operation **570**.

[0063] Other control signals are also required between PHY **170** and LINK **120**. These signals are as follows:

[0064] COMMA : signals the detection of K28.5 signal defined 8B10B coding, PHY to LINK

[0065] PARTIAL/SLUMBER : signals partial/slumber states, LINK to PHY

[0066] CLOCK : main system clock, PHY to LINK

5 [0067] COMINIT/COMWAKE : OOB (out of band) signaling

[0068] RESET : SATA related RESET

[0069] DATA READY : For handshaking purposes

[0070] TX_DATA_EN : For sending OOB data in Tx, LINK to PHY

[0071] Other signals : status report between PHY and LINK

10 [0072] Fig. 11 is a timing diagram illustrating a DATA_READY signal generation, in accordance with the present invention. For each channel of SATA devices, those signals can also be multiplexed. For example, DATA_READY signal is used for signaling whether the RX data is valid or noting this signal, the rate difference between RX and Tx can be controlled and only one synchronous clock can be used
15 for both Rx and Tx data. In the SATA implementation, a redundant ALIGN primitive is inserted. The PHY can either insert or delete these signals. Also, in order to make the deletion more simple, an additional data signal named DATA_READY can be used for both channels.

[0073] For lower frequency signals, they can be multiplexed by combining several
20 consecutive bits. In this case, a characteristic pattern can be used to multiplex those signals within normal data signals which is 8B10B encoded signal. For example, by combining 4 bits, signal activity can be defined as follows:

[0074] 1111 : alignment pattern

[0075] OXYZ : X, Y, Z is allocated for each bits for signaling.

[0076] In this case, each normal word except for the alignment pattern starts with o. X is used for the signal X, y is used for signal Y and Z is used for signal Z. For example X is RESET, Y and PARTIAL and Z is SLUMBER.

[0077] 0000: RESET is low, PARTIAL is low and SLUMBER is low

[0078] 0001 : RESET is low, PARTIAL is low and SLUMBER is high

[0079] By using these methods, the total number of signals to be used for supporting 2 channel SATA PHY can be minimized. One example for the usage of pins is shown in table 1.

[0080] Table 1. Pin number usage

Name	Number of pins	Purpose
TxD	10	LINK to PHY 10-bit data
TBC	1	Transmit byte clock
RXD	10	PHY to LINK 10-bit data
RBC0, RBC1	2	PHY to LINK byte clock
CTRL1	1	LINK to PHY control signals
CTRL2	1	PHY to LINK control signals
DATA_READY	1	DATA_READY signals
Total	26	

[0081] However, by using unused coding bytes for 8B10B coding in the TXD and RXD, those CTRL1, CTRL2 and DATA_READY can also be implemented. Then

the minimum set of data is only 25 pins. This will greatly reduce the overhead to implement both SATA channel and ATA channels in a chipset.

[0082] In the conventional ATA scheme, only one of the master or slave can have control of the ATA bus. By allowing two simultaneous communications of data, this method can boost the transport speed between the CPU and the HDD by a factor of two.

[0083] In view of the foregoing, it will be appreciated that a method for doubling a data rate on a disk drive serial bus includes developing a sampling data clock, developing a first data stream at a base data rate and developing a second data stream at the base data rate. The first data stream is multiplexed to a disk drive serial bus on a rising edge of the base data clock and the second data stream is multiplexed to the disk drive serial bus on a falling edge of the base data clock, whereby the disk drive serial bus carries both the first data stream and the second data stream at effectively double the base data rate.

[0084] Fig. 12 is a flowchart illustrating a method **580** encoding additional information in an unused coding space of a coding standard, in accordance with the present invention. After a start operation **590**, an unused coding space in a coding standard is determined at operation **600**. Some of the bits are then forced into the unused coding space at operation **610** and some of the remaining bits are used as an additional communication channel at operation **620**. Method **580** then ends at operation **630**.

[0085] Fig. 13A is a flowchart illustrating a method **650** for encoding additional information in an unused coding space of an 8B10B encoding scheme, in accordance with the present invention. After a start operation **650**, an 8 bit/10 bit encoding scheme is selected at operation **660**. At least six bits are forced to either

all one's ("111111") or all zero's ("000000"), at operation **670**. At least some of the remaining bits are then used for an additional communication channel at operation **680**. Method **640** then completes at operation **690**.

[0086] Fig. 13B is an illustration of encoding additional information in an unused coding space of an 8B10B encoding scheme, in accordance with the present invention. In example **700**, the first six bits were forced to "one". As previously mentioned, the occurrence of six consecutive one's signal that at least a portion of the remaining coding space is used for additional information. In this particular case, the additional information takes the form of "ABCD". Similarly, in example **710**, the first six bits were forced to "zero" and therefore the remaining coding space can be used to communicate additional data. It will be appreciated by one skilled in the art that the occurrence of the six consecutive one's or zero's can take place at any location within the coding space and the remaining unused portion can be used as the additional information channel.

[0087] In view of the foregoing, it will be appreciated that a method for encoding additional commands in a coding standard includes determining at least one invalid command in used coding space of a coding standard; and determining unused coding space. The at least one invalid command is encoded in the used coding space and at least one command is encoded in the unused coding space.

[0088] Fig. 14 is a block diagram **720** illustrating pin encoding, in accordance with an embodiment of the present invention. Included in block diagram **720** is a PHY **730** for providing communication between a dual-channel SATA PHY and a southbridge **30** with a SATA link and transport layer. The connections between PHY **730** and the southbridge **30** include TxD, TBC, RxD, RBC[0:1], RX_DATA_VALID, COM_DET, ASIC_CHK, RESET and REF. Also included in a

system clock **740**. The encircled connections labeled as SATALITE interface are the connections that utilize multiplexed signals.

[0089] Fig. 15 is a timing diagram **750** illustrating a method of transmitting a double data rate (DDR), in accordance with an embodiment of the present

5 invention. The data interface between the PHY **730** and the southbridge **30** runs at a double data rate. Since the bandwidth of operating two PHY's **730** (only one is shown for simplicity) at the first generation SATA speed of 1.5 gigabytes per second would require a total of 3.0 gigabytes per second. Therefore, a 10-bit bus would need to be sampled at 300 MHz with a conventional single data rate (SDR)
10 implementation. With DDR, a 150 MHz clock is used and both edges of the clock is sampled.

[0090] For the transmit case, the rising and falling edges of the TBC (transmit byte clock) and TxD (Tx data) are aligned. A high period **760** of the TBC signals TxD channel 0 data. Conversely, a low period **770** of the TBC indicates TXD channel 1
15 data.

[0091] For the receive case, only the rising edges are used for sampling. The rising edge **780** of RBC0 (receive byte clock 0) is used to latch RxD (Rx data). Similarly, the rising edge **790** of RBC1 is used RxD for channel 1.

[0092] Referring back to Fig. 14, the PHY **730** is capable of incorporating two
20 SATA channels. However, it is possible that only one SATA device would be connected. Therefore, given that situation, it is possible to employ various power savings techniques. Most of the power consumption of the SATALITE interface is due to I/O switching. The DDR mode is adopted to multiplex two SATA data streams and if only one SATA device is present, power would be wasted
25 multiplexing for a non-existent second SATA device. If only one SATA device is

connected, then TxD and RxD do not need to switch on the half cycles assigned to the unconnected channel. Therefore a SDR mode is employed when only one SATA device is connected.

5 [0093] In the interest of simplification, however, the TBC and RBC clocks are kept at the same rate and will now be further explained. Figs. 16-19 illustrate timing diagrams for an SDR case when channel 0 is active, an SDR case when channel 1 is active, illustrating RBC0 and RBC1 when channel 0 is active and RBC0 and RBC1 when channel 1 is active, respectively, all for a power saving mode in accordance with the present invention. Referring to figs. 16 and 18, only channel 0 is connected and channel 0 data is sampled on the high period **750** of TBC and the rising edge **760** of RBC0. Instead of switching the data to nulls for channel 1 on the low period **770** of TBC or the falling edge **780** of RBC0, the TxD/RxD pins (not shown) maintain the same data as sent for channel 0. As a result, toggling is done at 150 megabytes per second instead of 300 megabytes per second.

15 [0094] Conversely, figs. 17 and 19 convey the case where only channel 1 is active. Channel 1 data is sampled on the low period **790** of TBC and the falling edge **800** of RBC0. Also, instead of switching the data to nulls for channel 0 on the high period **810** of TBC or the rising edge **820** of RBC0, the TxD/RxD pins (not shown) maintain the same data as sent for channel 1. Again, toggling is done at 150
20 megabytes per second.

[0095] During the clock channels assigned to an inactive channel, the RX_DATA_VALID signal (see fig. 14) will go low in the receiver to indicate that the RxD outputs are not valid data for that channel. At the data multiplexer/demultiplexer (not shown), the invalid data can be dropped in the
25 single channel mode as it does not need to be propagated further. When both

channel 0 and 1 are inactive, the data pattern is unchanged and the power consumed becomes zero. In any of the preceding cases, however, TBC, RBC0 and RBC1 keep toggling.

[0096] In order to realize the power savings, state machines are required for each channel. Fig. 20 illustrates a state diagram **820** for channel 0 and channel 1 active/inactive modes, in accordance with the present invention. The default state for all state machines is active mode **830**. This can occur, for example, at power on or after an external RESET. When this happens, the southbridge **30** will send signals to the PHY **730** in an attempt to handshake with any connected devices. Transitions from the active mode **830** to the inactive mode **840** can be initiated from either the southbridge **30** or the PHY **730**. For example, a host may initiate activity via the southbridge **30** or the PHY **730** may initiate activity due to a device being hot-plugged. Host initiated activity occurs when the southbridge **30** sends a soft RESET command or a WAKE command to the inactive channel, either one is also preceded by an OOB sequence (COM_RESET or COM_WAKE). PHY **730** initiated transitions occur when a device sends a COM_INIT or a COM_WAKE that is detected by the PHY **720** and passed along to the southbridge **30**. It will be appreciated by those skilled in the art that each of the WAKE, RESET, COM_INIT and COM_WAKE commands is channel specific. When both channels are active, the SATALITE interface exchanges data in the DDR mode.

[0097] Fig. 21 is a block diagram of an SATA PHY **730**, in accordance with the present invention. Included in SATA PHY **730** is an input latch **850** coupled to a Tx decoder-0 **860** and a Tx decoder-1 **870** both of which are coupled to serializers **880**, respectively. Additionally, there are deserializers **890** coupled to OOB detectors **900**. Each deserializer **890** is coupled to an Rx encoder-0 **910** and an Rx encoder-1 **920**, respectively. Rx encoder-0 **910** and an Rx encoder-1 **920** are both

coupled to data output **950**. Phase lock loop (PLL) **940** coupled to the serializers **880**, deserializers **890** and the ASIC_CK_RATE **930**. PLL **940** is used for synchronizing the various system clocks contained in the SATA PHY **730**. Finally control **960** is coupled to REXT and RESET inputs. It will be appreciated by one skilled in the art that many aspects of the SATA PHY **730** are a standard implementation conforming to serial ATA guidelines and Intel corporation's SAPIs (SATA PHY Interface Specification) guidelines. As such, SATA PHY **730** will not be described in exhaustive detail as to not unnecessarily obscure the present invention.

10 [0098] Fig. 22 is a detailed block diagram illustrating the hookup of the Rx encoders **910** and **920** with a two-channel interface, in accordance with the present invention. Rx encoder-0 **910** is coupled to RX_ERROR0 , RX_LOCKED0, Underflow1, Sig_level_valid0 and Com_init0/com_wake0 inputs. Sig_level_valid0 and Com_init0/com_wake0 inputs are also coupled to an encoding condition
15 detection block **970**. Outputs from Rx encoder-0 **910** and encoding condition detection **970** are coupled to mux **980**. Mux **980** is also coupled to RXD_IN0[0:9].

[0099] In a similar fashion, Rx encoder-1 **920** is coupled to RX_ERROR1 , RX_LOCKED1, Underflow1, Sig_level_valid1 and Com_init1/com_wake1 inputs. Sig_level_valid1 and Com_init1/com_wake1 inputs are also coupled to an
20 encoding condition detection block **970**. Outputs from Rx encoder-1 **920** and encoding condition detection **970** are coupled to mux **990**. Mux **980** is also coupled to RXD_IN1[0:9]. SDR (single data rate) / DDR (double data rate) conversion block **1000** is coupled to outputs of flipflops **980** and **990**, ch0_act and ch1_act. SDR/DDR conversion block **1000** has an RXD[0:9] and sig_level_valid outputs.

[00100] Fig. 23A is a detailed block diagram illustrating the hookup of the Tx encoders **860** and **870** with a two-channel interface, in accordance with the present invention. 90 degree delay block **1030** is coupled to a TBC input. FFs **1010** and **1020** are both coupled an output of the 90 degree delay block **1030** and TXD[0:9].
 5 Tx decoder-0 **860** is coupled to the output of FFs **1010** – Txd[0:9]. Similarly, Tx decoder-1 **870** is coupled to the output of multiplexer **1020** – TxD1[0:9]. By delaying the TBC by 90 degrees, or one quarter of a cycle, the rising and falling edges of TBC latch Tx0 and Tx1.

[00101] Fig. 23B is a more detailed block diagram illustrating the hookup of
 10 the Tx encoders **1040**, in accordance with the present invention. An error code-box **1050** outputs either “111111” or “000000” into the TxD[0:5] coding space. When either is output, it is a signal that the remaining unused coding space is to be used for additional commands. To achieve this, TxD[6:9] is coupled to a coding table **1060**. Coding table **1060** contains the available commands that can be inserted into
 15 the unused coding space. The output of the coding table **1060**, a constant and the output of error code-box **1050** form the inputs of flipflop **1070**.

[00102] An advantage of the present invention is that serial ATA hard disk drives can be added to an existing system utilizing ATA hard disk drives without adding to the pin count of a chipset. Additionally, the present invention provides
 20 for double data rate communication to serial ATA hard disk drives and for encoding additional commands in an unused space of a coding standard.

[00103] An advantage of the present invention is that serial ATA hard disk drives can be added to an existing system utilizing ATA hard disk drives without adding to the pin count of a chipset. Additionally, the present invention provides

for double data rate communication to serial ATA hard disk drives and for encoding additional commands in an unused space of a coding standard.

[00104] While this invention has been described in terms certain preferred embodiments, it will be appreciated by those skilled in the art that certain
5 modifications, permutations and equivalents thereof are within the inventive scope of the present invention.